



HIGHLY EFFICIENT


Yingli PANDA YL255C-30b, YL260C-30b, YL265C-30b

MONOCRYSTALLINE SOLAR MODULES


The latest technology helps to keep the Yingli PANDA YLxxxC-30b series “young.” These solar modules offer particularly high efficiency for their size – over a long period of time. They are manufactured based on n-type silicon. They stand out for their better low-light and thermal behavior. In addition, the use of three busbars reduces electrical losses.

HIGHLIGHTS

- Suitable for grid-connected systems
- Tested according IEC 61215 for snow loads up to 5400 Pa (ca. 550 kg/m²) (in process)
- Power tolerance +3%/-3%
- Power warranties*
 - 10 years (90%)
 - 25 years (80%)
- 5-year product warranty*
- IEC 61730, Application Class A for system voltages up to 1,000 V
- IEC 61215 tested and certified
- Produced in ISO 9001- and 14001-certified factories
- 100% end control with individual registration of the electrical characteristics



Progression of the power warranty



TECHNICAL DATA

Yingli PANDA	255C-30b	260C-30b	265C-30b
STC Power Pmax (Wp)	255	260	265
STC Nominal Voltage Umpp (V)	30,6	30,8	31,0
STC Nominal Current Impp (A)	8,33	8,46	8,55
STC Open circuit voltage Uoc (V)	38,2	38,6	39,0
STC Short circuit current Isc (A)	8,85	8,91	8,93
800 W/m ² NOCT AM1.5 Power Pmax (Wp)	185,2	188,8	192,4
800 W/m ² NOCT AM1.5 Nominal Voltage Umpp (V)	27,7	27,8	28,1
800 W/m ² NOCT AM1.5 Open Circuit Voltage Uoc (V)	35,2	35,5	35,9
800 W/m ² NOCT AM1.5 Short Circuit Current Isc (A)	7,13	7,18	7,20
Rel. efficiency reduction @ 200W/m ² (%)	5	5	5
Tempcoeff Isc (%/°C)	+0,04	+0,04	+0,04
Tempcoeff Uoc (mV/°C)	-126	-127	-128
Tempcoeff Pmpp (%/°C)	-0,45	-0,45	-0,45
Module Efficiency (%)	15,6	15,9	16,2
NOCT °C	46	46	46
Max. System Voltage (V)	1000	1000	1000
Current value String fuse (A)	15	15	15
Fuse protection from parallel strings	4	4	4
Length (mm)	1650	1650	1650
Width (mm)	990	990	990
Height (mm)	50	50	50
Weight (kg)	19,5	19,5	19,5
Articlenumber	2001700004	2001700003	2001700007

Your IBC SOLAR partner:

13.09.2011

* Product and power warranty in accordance with the version of the full warranty conditions received from your specialized IBC SOLAR partner at the time of installation. This warranty is valid only when the relevant product is installed in accordance with the applicable installation instructions. Electrical values under standard test conditions: 1000W/m²; 25°C, AM1.5, 800 W/m², NOCT. Specifications according EN60904-3 (STC). All datas according DIN EN 50380. Subject to modifications that represent process.